

# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20180703-E176375  
**Report Reference** E176375-20080624  
**Issue Date** 2018-JULY-03

**Issued to:** GARNER OSBORNE CIRCUITS LTD  
UNIT 10  
HAMBRIDGE BUSINESS CENTRE  
HAMBRIDGE LANE  
NEWBURY, BERKSHIRE RG14 5TU UNITED KINGDOM

**This is to certify that representative samples of** Wiring, Printed - Component  
Multilayer printed wiring boards. Type 3.  
(See Addendum for Additional Information.)

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** Standard for Tests for Safety for Printed-Wiring Boards, UL 796  
Standard for Evaluation of Properties of Polymeric Materials  
CAN CSA 22.2 No. 0.17

**Additional Information:** See the UL Online Certifications Directory at [www.ul.com/database](http://www.ul.com/database) for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for use as components of complete equipment submitted for investigation rather than for direct separate installation in the field. The final acceptance of the component is dependent upon its installation and use in complete equipment submitted to UL LLC.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Assistant Chief Engineer, Global Inspection and Field Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at [www.ul.com/contactus](http://www.ul.com/contactus)



# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20180703-E176375  
**Report Reference** E176375-20080624  
**Issue Date** 2018-JULY-03

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Addendum –

	Cond Width				Max			Max			
	Min	Cond	SS/	Area	Solder	Oper		Meets	C		
	Min	Edge	Thk	DS/	Diam	Limits	Temp	Flame	UL796	T	
Type	mm(in)	mm(in)	mic(mil)	DSO	mm(in)	C	sec	C	Class	DSR	I
Multilayer printed wiring boards.											
3	0.093 (0.004)	0.279 (0.011)	16.5 (0.65) Int:66	DS	50.8 (2.0)	260	20	130	V-0	All	*



Bruce Mahrenholz, Assistant Chief Engineer, Global Inspection and Field Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at [www.ul.com/contactus](http://www.ul.com/contactus)

